

Declaration of Performance

No. 003/DoP/20200701

In accordance with regulation (EU) No 305/2011 of the European parliament and of the Council laying down harmonized conditions for the marketing of construction products (CPR EU 305/2011)

1. Unique identification code of the product-type:

Fibre-cement flat sheets

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

SCG Smartboard

≥4 mm

(The Production Batch Number will be provided by the manufacturer, and will be printed on the back of the product using laser jet printing)

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Cladding for external and internal walls

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Siam Fibre-Cement Co., Ltd.
1 Siam Cement Road, Bangsue
Bangkok 10800, Thailand
Tel: +66 2586 2222, Fax: +66 2586 6532
Mail: contact@scg.com, Website: www.scgbuildingmaterials.com

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

BMC Danmark
Stykgodsvej 7
DK-9000 Aalborg
Tlf. +45 96 31 28 00
Mail: bmc@bmc-danmark.dk , Website: www.bmc-danmark.dk

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 3

7. Name and identification of the notified body (In case of the declaration of performance concerning a construction product covered by a harmonized standard):



The initial type testing was performed by:
SCG Building Materials Co., Ltd. (SCG Report 2017TDC0001)
VTT Expert Services Ltd. (Test Report No. VTT-S-00226-18)

Reaction to fire test and classification according to EN 13501-1 was performed by:
TÜV SÜD PSB Pte. Ltd., Singapore 118221 (Classification Report No. 7191207143-MEC19/3-JV)

8. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Type of sheets	NT	EN 12467:2012
Mechanical resistance	Category A, Class 2	
Apparent density	1330 kg/m ³	
Reaction to fire*	A2-s1,d0	
Water impermeability	Pass	
Dimensional variations	Level 1	
Release of dangerous substances	-	
Durability against warm water	RL >0.75	
Durability against soak/dry	RL >0.75	
Durability against freeze/thaw	RL >0.75	
Durability against heat/rain	Pass	

*EN13501-1:2007+A1:2009

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Name: Per Kjær Nielsen
Title: Sales director
Place and date: Aalborg, 01.07.2020
Signature:

